



0620

Hertalan Rubber Products bv, Industrieweg 16, NL 8263AD, Kampen
07
0620-CPD-44520

EN 13956

hertalan easy.cover, EPDM.

Thickness: 1,00 mm

Other dimensions in conformity with the delivery specifications.

Application:

Covered roof: balasted.

External fire performance: not relevant

Reaction to fire: No performance determined

Watertightness: Pass

Tensile strength in longitudinal and transverse direction: 8 N/mm²

Elongation in longitudinal and transverse direction: 400%

Resistance to impact on hard support: 250 mm

Resistance to impact on soft support: 2000 mm

Resistance to static loading on hard and soft support: 20 kg

Tear resistance: 25N

Joint peel resistance: 25 N/50 mm

Joint shear resistance: 200 N/50 mm

Dimensional stability: -0,2%

Foldability at low temp.: -70°C

Durability after UV exposure: Grade 0, -70°C

Exposure to bitumen: Pass

The product does not contain dangerous substances



0620

Hertalan Rubber Products bv, Industrieweg 16, NL 8263AD, Kampen
07
0620-CPD-44520

EN 13956

hertalan easy.cover, EPDM.

Thickness: 1,00 mm

Other dimensions in conformity with the delivery specifications.

Application:

Covered roof: balasted.

External fire performance: not relevant

Reaction to fire: No performance determined

Watertightness: Pass

Tensile strength in longitudinal and transverse direction: 8 N/mm²

Elongation in longitudinal and transverse direction: 400%

Resistance to impact on hard support: 250 mm

Resistance to impact on soft support: 2000 mm

Resistance to static loading on hard and soft support: 20 kg

Tear resistance: 25N

Joint peel resistance: 25 N/50 mm

Joint shear resistance: 200 N/50 mm

Dimensional stability: -0,2%

Foldability at low temp.: -70°C

Durability after UV exposure: Grade 0, -70°C

Exposure to bitumen: Pass

The product does not contain dangerous substances